SAFETY: STAINLESS STEEL PRODUCTS

SAFETY HOOK SYSTEMS

MAKEFAST DOUBLE ACTION SAFETY HOOK

The revolutionary Makefast Safety Hook surpasses all current standards in providing absolute security in all situations. Unlike other products the Makefast Safety Hook cannot be inadvertently opened, because of our unique double action locking system.

- Fixes to attachments up to 19mm (0.75 inches) in diameter
- Unique double action safety locking system
- Impossible to open accidentally
- Single handed operation

The Makefast Safety Hook prevents accidental opening by using a DOUBLE ACTION LOCK.
If one lever is opened the hook DOES NOT OPEN. Both locks must be operated to open.





15KN

Part number 0200 - Specifications	
CE Marked To:	BS EN. 362 & 364 Personal Protective Equipment
	EN.1095 Para. 4.3.5. Deck Safety Harness And Safety Line For Use On Recreational Craft
Materials	Type 316 Stainless steel for hook, gate and locks Nylon 6 (A28GM) for protective fairing
Weight	180g
Loading	Withstands static strength test of 15kn (3300lbs) (fully operational)
	Withstands static strength test of 20kn (4400lbs) (non operational)
Finish	Plastic fairing provides secure grip & reduces deck damage if dropped
Operation	Double action lock, single handed
Fixing	Hook can be secured to tube up to 19mm (0.75inches) diameter
Slot	Suitable for 25mm (1 inch) webbing or 16mm (0.63inches) rope
Colours	Red, black, blue, high visibility yellow (other colours to order)



Part No. 0200 Safety Hook with 15KN working load